





# bizhub 458e

#### **Customer benefits**



Intuitive operability Operate the bizhub like a smartphone or tablet with fully customised user interface



Security Secure network integration. data encryption, HDD overwrite, and advanced user authentication



Application ecosystem Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio



Productivity

Reliability, high-speed scanning and printing, combined with powerful finishing functions



#### Accessibility

Seamless operation of your bizhub device and valuable support for easier access and handling to suit users with special needs



Efficient printer fleet management. including automatic consumables delivery, pro-active maintenance and remote setup

#### **Options**



OCR text recognition LK-105v4

Barcode fonts LK-106

Unicode fonts LK-107

OCR A and B fonts LK-108

**Document converter pack** LK-110v2

ThinPrint® client

Serverless pull printing LK-114

Trusted Platform Module activation LK-115v2





**Double feed detection kit** UK-501

Air cleaning unit

Hard disk mirroring HD-524

Security kit SC-508

Working table WT-506

**10-Key pad** KP-101



**1 x Universal tray** PC-115

2 x Universal tray PC-215

Large capacity tray PC-415

Copier desk DK-510

Large capacity tray LU-302

Large capacity tray

Banner tray BT-C1e

### 2 CONNECTIVITY

Fax board FK-514 Wireless LAN SX-BR-4600

Wireless LAN

Biometric authentication AU-102

#### **ID** card reader

Mount kit MK-735

USB I/F kit EK-608 USB I/F kit

EK-609 **Keyboard holder** KH-102 5 MEDIA OUTPUT

Job separator

Output tray 0T-506

Inner finisher FS-533

**Staple finisher** FS-536

Relay unit RU-513

Staple/booklet finisher Relay unit RU-513

Punch kit

Staple finisher FS-537

Relay unit RU-513

Staple/booklet finisher

Relay unit RU-513

**Z-fold unit** ZU-609

Punch kit PK-523

Post inserter PI-507

Job separator

#### **LEGEND**

Mandatory option Option This option can

with the respective option above it

#### **Finishing functionalities**









punching



punching





mixplex/







insertion,

report





**Booklet** 



OR



Z-fold



printing

## **Descriptions**

### bizhub 458e

A3 multifunctional with 45 ppm b/w. Standard Emperon™ print controller with PCL 6, PCL 5, PostScript 3, PDF 1.7, XPS and OOXML support. Paper capacity of 500 + 500 sheets and 150-sheet manual bypass. Media from A6 to SRA3, 1.2 m banner and  $52 - 300 \text{ g/m}^2$ . 4 GB memory, 250 GB hard disk and Gigabit Ethernet standard.

#### **ENHANCED FEATURES**

LK-102v3 PDF enhancements	PDF/A; PDF encryption; digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document	Generates various file formats incl. DOCX; XLSX and PDF/A
converter pack	
LK-111 ThinPrint® Client	Print data compression for reduced network impact
LK-114 Serverless pull printing	Secure and Follow Me printing solution
	requiring no server application.
LK-115v2 TPM activation	Trusted Platform Module for protection of data encryption
	and decryption

#### CONNECTIVITY

001111201111111	
FK-514 Fax board	Super G3 fax, digital fax functionality
SX-BR-4600 Wireless LAN	Wireless LAN to network connector
AU-102 Biometric authentication	Finger vein scanner
UK-215 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
KH-102 Keyboard holder	To place USB keyboard

### **OTHERS**

UK-501 Double feed detection kit	Multi-feed detector to reduce errors and paper jams
CU-102 Air cleaning unit	Improving indoor air quality by reduced emissions
WT-506 Working table	Authentication device placement
KP-101 10-Key pad	For use instead of touchscreen
SC-508 Security kit	Copy Guard function (2 kits required)
HD-524 Hard disk mirroring	Back-up HDD
MEDIA INPUT	
PC-115 1 x Universal tray	A5-A3, 500 sheets, 52-256 g/m <sup>2</sup>
PC-215 2 x Universal tray	A5-A3, 2 x 500 sheets, 52-256 g/m <sup>2</sup>
PC-415 Large capacity tray	A4, 2,500 sheets, 52–256 g/m <sup>2</sup>
LU-302 Large capacity tray	A4, 3,000 sheets, 52–256 g/m <sup>2</sup>
LU-207 Large capacity tray	A4-SRA3; 2,500 sheets; 52-256 g/m <sup>2</sup>
BT-C1e Banner tray	Multipage banner feeding
DK-510 Copier desk	Provides storage space for print media and other materials
MEDIA OUTPUT	
JS-506 Job separator	Separation of fax output; etc.
	Separation of fax output; etc. Output tray used instead of finisher
JS-506 Job separator	
JS-506 Job separator OT-506 Output tray	Output tray used instead of finisher
JS-506 Job separator OT-506 Output tray RU-513 Relay unit FS-536 Staple finisher	Output tray used instead of finisher  For FS-536/SD or FS-537/SD installation (Max. 100 sheets output capacity)  50-sheet stapling, 3,200 sheets max. output
JS-506 Job separator OT-506 Output tray RU-513 Relay unit	Output tray used instead of finisher For FS-536/SD or FS-537/SD installation (Max. 100 sheets output capacity)
JS-506 Job separator OT-506 Output tray RU-513 Relay unit FS-536 Staple finisher FS-536SD Staple/booklet finisher	Output tray used instead of finisher  For FS-536/SD or FS-537/SD installation (Max. 100 sheets output capacity)  50-sheet stapling, 3,200 sheets max. output  50-sheets staple finisher, 20-sheets booklet finisher,  2,200 sheets max. output
JS-506 Job separator 0T-506 Output tray RU-513 Relay unit FS-536 Staple finisher FS-536SD Staple/booklet finisher PK-520 Punch kit for FS-536(SD)	Output tray used instead of finisher  For FS-536/SD or FS-537/SD installation (Max. 100 sheets output capacity)  50-sheet stapling, 3,200 sheets max. output  50-sheets staple finisher, 20-sheets booklet finisher,  2,200 sheets max. output  2/4 hole punching, autoswitching
JS-506 Job separator OT-506 Output tray RU-513 Relay unit FS-536 Staple finisher FS-536SD Staple/booklet finisher	Output tray used instead of finisher  For FS-536/SD or FS-537/SD installation (Max. 100 sheets output capacity)  50-sheet stapling, 3,200 sheets max. output  50-sheets staple finisher, 20-sheets booklet finisher,  2,200 sheets max. output
JS-506 Job separator 0T-506 Output tray RU-513 Relay unit FS-536 Staple finisher FS-536SD Staple/booklet finisher PK-520 Punch kit for FS-536(SD)	Output tray used instead of finisher  For FS-536/SD or FS-537/SD installation (Max. 100 sheets output capacity)  50-sheet stapling, 3,200 sheets max. output  50-sheets staple finisher, 20-sheets booklet finisher, 2,200 sheets max. output  2/4 hole punching, autoswitching  100 sheets stapling; 3,200 sheets max. output  100-sheets staple finisher; 20-sheets booklet finisher;
JS-506 Job separator OT-506 Output tray RU-513 Relay unit FS-536 Staple finisher FS-536SD Staple/booklet finisher PK-520 Punch kit for FS-536(SD) FS-537 Staple finisher FS-537SD Staple/booklet finisher	Output tray used instead of finisher  For FS-536/SD or FS-537/SD installation (Max. 100 sheets output capacity)  50-sheet stapling, 3,200 sheets max. output  50-sheets staple finisher, 20-sheets booklet finisher, 2,200 sheets max. output  2/4 hole punching, autoswitching  100 sheets stapling; 3,200 sheets max. output  100-sheets staple finisher; 20-sheets booklet finisher; 2,700 sheets max. output
JS-506 Job separator OT-506 Output tray RU-513 Relay unit FS-536 Staple finisher FS-536SD Staple/booklet finisher PK-520 Punch kit for FS-536(SD) FS-537 Staple finisher FS-537SD Staple/booklet finisher	Output tray used instead of finisher  For FS-536/SD or FS-537/SD installation (Max. 100 sheets output capacity)  50-sheet stapling, 3,200 sheets max. output  50-sheets staple finisher, 20-sheets booklet finisher, 2,200 sheets max. output  2/4 hole punching, autoswitching  100 sheets stapling; 3,200 sheets max. output  100-sheets staple finisher; 20-sheets booklet finisher; 2,700 sheets max. output  Z-fold for A3 prints
JS-506 Job separator OT-506 Output tray RU-513 Relay unit  FS-536 Staple finisher FS-536SD Staple/booklet finisher  PK-520 Punch kit for FS-536(SD) FS-537 Staple finisher FS-537SD Staple/booklet finisher  ZU-609 Z-fold unit for FS-537/SD PK-523 Punch kit for FS-537/SD	Output tray used instead of finisher  For FS-536/SD or FS-537/SD installation (Max. 100 sheets output capacity)  50-sheet stapling, 3,200 sheets max. output  50-sheets staple finisher, 20-sheets booklet finisher, 2,200 sheets max. output  2/4 hole punching, autoswitching  100 sheets stapling; 3,200 sheets max. output  100-sheets staple finisher; 20-sheets booklet finisher; 2,700 sheets max. output  Z-fold for A3 prints  2/4 hole punching; autoswitching
JS-506 Job separator OT-506 Output tray RU-513 Relay unit FS-536 Staple finisher FS-536SD Staple/booklet finisher PK-520 Punch kit for FS-536(SD) FS-537 Staple finisher FS-537SD Staple/booklet finisher ZU-609 Z-fold unit for FS-537/SD PK-523 Punch kit for FS-537/SD PI-507 Post inserter for FS-537/SD	Output tray used instead of finisher  For FS-536/SD or FS-537/SD installation (Max. 100 sheets output capacity) 50-sheet stapling, 3,200 sheets max. output 50-sheets staple finisher, 20-sheets booklet finisher, 2,200 sheets max. output 2/4 hole punching, autoswitching 100 sheets stapling; 3,200 sheets max. output 100-sheets staple finisher; 20-sheets booklet finisher; 2,700 sheets max. output Z-fold for A3 prints 2/4 hole punching; autoswitching
JS-506 Job separator OT-506 Output tray RU-513 Relay unit FS-536 Staple finisher FS-536SD Staple/booklet finisher PK-520 Punch kit for FS-536(SD) FS-537 Staple finisher FS-537SD Staple/booklet finisher ZU-609 Z-fold unit for FS-537/SD PK-523 Punch kit for FS-537/SD PI-507 Post inserter for FS-537/SD JS-602 Job separator for FS-537/S	Output tray used instead of finisher  For FS-536/SD or FS-537/SD installation (Max. 100 sheets output capacity) 50-sheet stapling, 3,200 sheets max. output 50-sheets staple finisher, 20-sheets booklet finisher, 2,200 sheets max. output 2/4 hole punching, autoswitching 100 sheets stapling; 3,200 sheets max. output 100-sheets staple finisher; 20-sheets booklet finisher; 2,700 sheets max. output Z-fold for A3 prints 2/4 hole punching; autoswitching 0 Cover insertion; post finishing 0 Separation of fax output; etc.
JS-506 Job separator OT-506 Output tray RU-513 Relay unit FS-536 Staple finisher FS-536SD Staple/booklet finisher PK-520 Punch kit for FS-536(SD) FS-537 Staple finisher FS-537SD Staple/booklet finisher ZU-609 Z-fold unit for FS-537/SD PK-523 Punch kit for FS-537/SD PI-507 Post inserter for FS-537/SD	Output tray used instead of finisher  For FS-536/SD or FS-537/SD installation (Max. 100 sheets output capacity) 50-sheet stapling, 3,200 sheets max. output 50-sheets staple finisher, 20-sheets booklet finisher, 2,200 sheets max. output 2/4 hole punching, autoswitching 100 sheets stapling; 3,200 sheets max. output 100-sheets staple finisher; 20-sheets booklet finisher; 2,700 sheets max. output Z-fold for A3 prints 2/4 hole punching; autoswitching

### **Technical specifications**

#### SYSTEM SPECIFICATIONS

Panel size/resolution	9" / 800 x 480
System memory (standard/max)	4,096 MB
System hard disk	250 GB (standard)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11b/g/n (optional)
Network protocols	TCP/IP (IPv4 / IPv6); NetBEUI; SMB; LPD; IPP; SNMP; HTTP
Automatic document feeder	Up to 300 originals; A6-A3; 35-210 g/m²; Dualscan ADF
(standard)	
Printable paper size	A6-SRA3; customised paper sizes;
	banner paper max. 1,200 x 297 mm
Printable paper weight	52–300 g/m²
Paper input capacity (standard/max)	1,150 sheets/6,650 sheets
Paper tray input (standard)	1x 500 sheets; A5–A3; 52–256 g/m²;
	1x 500 sheets; A5–SRA3; 52–256 g/m²
Paper tray input (optional)	1x 500 sheets; A5–A3; 52–256 g/m²;
	2x 500 sheets; A5-A3; 52-256 g/m²;
	1x 2,500 sheets; A4; 52–256 g/m <sup>2</sup>
Large capacity tray (optional)	1x 3,000 sheets; A4; 52–256 g/m²;
	1x 2,500 sheets; A4-SRA3; 52-256 g/m <sup>2</sup>
Manual bypass	150 sheets; A6-SRA3; custom sizes; banner; 60-300 g/m²
Automatic duplexing	A6 portrait; A5-SRA3; 52-256 g/m <sup>2</sup>
Finishing modes (optional)	Offset; group; sort; staple; punch; post insertion; half-fold;
	letter-fold; booklet; z-fold
Output capacity (standard)	Max. 250 sheets
Output capacity (optional)	Max. 3,300 sheets
Stapling	Max. 100 sheets or 94 sheets $+$ 2 cover sheets (up to 209 g/m <sup>2</sup> )
Stapling output capacity	Max. 1,000 sheets
Letter fold	Max. 3 sheets

Letter fold capacity	Max. 30 sheets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 209 g/m²)
Booklet output capacity	Max. 100 sheets; unlimited (without tray)
Copy/print volume (monthly)	Rec. 30,000 pages; Max. 200,000 pages <sup>1</sup>
Toner lifetime	Up to 26,000 pages
Imaging unit lifetime	Up to 275,000/600,000 pages (drum/developer)
Power consumption	220-240 V / 50/60 Hz; Less than 2 kW
System dimension (W x D x H)	615 x 755 x 961 mm (without options)
System weight	Approx. 96 kg (without options)

PRINTER SPECIFICATIONS	
Print resolution	1,800 x 600 dpi; 1,200 x 1,200 dpi
Page description language	PCL 6 (XL 3.0); PCL 5; PostScript 3 (CPSI 3016); XPS
Operating System	Windows 7 (32/64); Windows 8/8.1 (32/64);
	Windows 10 (32/64); Windows Server 2008 (32/64);
	Windows Server 2008 R2; Windows Server 2012;
	Windows Server 2012 R2; Windows Server 2016;
	Macintosh OS X 10.8 or later; Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Print functions	Direct print of PCL, PS, TIFF, XPS, PDF (v1.7), encrypted
	PDF files and OOXML (DOCX, XLSX, PPTX); mixmedia and
	mixplex; "Easy Set" job programming; overlay; watermark;
	copy protection; carbon copy print
Mobile printing	AirPrint (iOS); Mopria (Android); Konica Minolta Print Service
	(Android); Konica Minolta Mobile Print (iOS/Android/Windows 10
	Mobile); Mobile Authentication and Pairing (iOS/Android)
	optional: Google Cloud Print; WiFi Direct

#### SCANNER SPECIFICATIONS

Up to 120 ipm in simplex; Up to 240 ipm in duplex Up to 600 x 600 dpi Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-to-DPWS; Scan-to-URL; TWAIN scan
Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-to-DPWS; Scan-to-URL;
to-Home); Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-to-DPWS; Scan-to-URL;
Scan-to-WebDAV; Scan-to-DPWS; Scan-to-URL;
TWAIN coop
I WAIIV Scall
JPEG; TIFF; PDF; compact PDF; encrypted PDF; XPS;
compact XPS; PPTX
optional: searchable PDF; PDF/A 1a and 1b;
searchable DOCX/PPTX/XLSX
2,100 (single + group); LDAP support
Annotation (text/time/date) for PDF; up to 400 job
programs; real-time scan preview

#### COPIER SPECIFICATIONS

OUI ILIT OF LUIT TOATTONS	
Imaging technology	Laser
Toner technology	Simitri® HD polymerised toner/Polymerised toner
Copy/print speed A4	Up to 45 ppm
Copy/print speed A3	Up to 22 ppm
Autoduplex speed A4	Up to 45 ppm
1st copy out time A4	4.0 sec.
Warm-up time	Approx. 20 sec. <sup>2</sup>
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–9,999
Original format	A5-A3; custom sizes
Magnification	25-400% in 0.1% steps; auto-zooming
Copy function	Chapter; cover and page insertion; proof copy
	(print and screen); adjustment test print; digital art
	functions; job setting memory; poster mode; image
	repeat; overlay; stamping; copy protection

FAX SPECIFICATIONS	
Fax standard	Super G3 (optional)
Fax transmission	Analogue; i-Fax; Colour i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,100 (single + group)
Fax functions	Polling; time shift; PC-Fax; receipt to confidential box;
	Pacaint to a mail/ETD/CMR: up to 400 job programs

#### USER BOX SPECIFICATIONS

OOLIT DON OF LOW TOATTONG	
Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt;
	Fax polling
User box functions	Reprint; combination; Download;
	Sending (e-mail/FTP/SMB and Fax); Copy box to box
SYSTEM FEATURES	
Security	ISO15408 Common Criteria (in evaluation); IP filterinç
	and port blocking; SSL2; SSL3 and TLS 1.0/1.1/1.2
	network communication; IPsec support; IEEE 802.1x
	support; User authentication; Authentication log;
	Secure print; Kerberos; Hard disk overwrite
	(8 standard types); Hard disk data encryption (AES
	256); Memory data auto deletion; Confidential fax
	receipt; Print user data encryption
	optional: Hard disk mirroring; Copy protection (Copy
	Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support
	(user name + password + e-mail + smb folder); User
	function access definition; Authentication by mobile
	device (Android/iOS)
	optional: Biometric authentication (finger vein
	scanner); ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager; PageScope
	Data Administrator; PageScope Box Operator;
	PageScope Direct Print; Print Status Notifier; Driver
	Packaging Utility; Log Management Utility

 $<sup>^{\</sup>rm 1}$  If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

- All specifications refer to A4-size paper of 80 g/m² quality.
   The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (6% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
   Specifications and accessories are based on the information available at the time of printing and are subject to
- change without notice.

   Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



































<sup>&</sup>lt;sup>2</sup> Warm-up time may vary depending on the operating environment and usage